

AS568 O-ring Reference guide.

ELPLASTO INNOVATIONS

Dash #	Nominal Cross Section: 1/16"		Actual: 0.070 ± .003 in 1.78 ± .08 mm			
000			Actual ID			
	Nominal (Inches)					
Size	ID	OD	in	±	mm	±
001	1/32	3/32	0.029	0.004	0.74	0.10
002	3/64	9/64	0.042	0.004	1.07	0.10
003	1/16	3/16	0.056	0.004	1.42	0.10
004	5/64	13/16	0.070	0.005	1.78	0.13
005	3/32	7/32	0.101	0.005	2.57	0.13
006	1/8	1/4	0.114	0.005	2.90	0.13
007	5/32	9/32	0.145	0.005	3.68	0.13
008	3/16	5/16	0.176	0.005	4.47	0.13
009	7/32	11/32	0.208	0.005	5.28	0.13
010	1/4	3/8	0.239	0.005	6.07	0.13
011	5/16	7/16	0.301	0.005	7.65	0.13
012	3/8	1/2	0.364	0.005	9.25	0.13
013	7/16	9/16	0.426	0.005	10.82	0.13
014	1/2	5/8	0.489	0.005	12.42	0.13
015	9/16	11/16	0.551	0.007	14.00	0.18
016	5/8	3/4	0.614	0.009	15.60	0.23
017	11/16	13/16	0.676	0.009	17.17	0.23
018	3/4	7/8	0.739	0.009	18.77	0.23
019	13/16	15/16	0.801	0.009	20.35	0.23
020	7/8	1	0.864	0.009	21.95	0.23
021	15/16	1-1/16	0.926	0.009	23.52	0.23
022	1	1.125	0.989	0.010	25.12	0.25
023	1-1/16	1-3/16	1.051	0.010	26.70	0.25
024	1-1/8	1-1/4	1.114	0.010	28.30	0.25
025	1-3/16	1-5/16	1.176	0.011	29.87	0.28
026	1-1/4	1-3/8	1.239	0.011	31.47	0.28
027	1-5/16	1-7/16	1.301	0.011	33.05	0.28
028	1-3/8	1-1/2	1.364	0.013	34.65	0.33
029	1-1/2	1-5/8	1.489	0.013	37.82	0.33
030	1-5/8	1-3/4	1.614	0.013	41.00	0.33
031	1-3/4	1-7/8	1.739	0.015	44.17	0.38
032	1-7/8	2	1.864	0.015	47.35	0.38
033	2	2-1/8	1.989	0.018	50.52	0.46
034	2-1/8	2-1/4	2.114	0.018	53.70	0.46
035	2-1/4	2-3/8	2.239	0.018	56.87	0.46
036	2-3/8	2-1/2	2.364	0.018	60.05	0.46
037	2-1/2	2-5/8	2.489	0.018	63.22	0.46
038	2-5/8	2-3/4	2.614	0.020	66.40	0.51
039	2-3/4	2-7/8	2.739	0.020	69.57	0.51
040	2-7/8	3	2.864	0.020	72.75	0.51
041	3	3-1/8	2.989	0.024	75.92	0.61
042	3-1/4	3-3/8	3.239	0.024	82.27	0.61
043	3-1/2	3-5/8	3.489	0.024	88.62	0.61
044	3-3/4	3-7/8	3.739	0.027	94.97	0.69
045	4	4-1/8	3.989	0.027	101.32	0.69
046	4-1/4	4-3/8	4.239	0.030	107.67	0.76
047	4-1/2	4-5/8	4.489	0.030	114.02	0.76
048	4-3/4	4-7/8	4.739	0.030	120.37	0.76
049	5	5-1/8	4.989	0.037	126.72	0.94
050	5-1/4	5-3/8	5.239	0.037	133.07	0.94

AS568 O-ring Reference guide.

ELPLASTO INNOVATIONS

Dash #	Nominal Cross Section: 3/32"		Actual: .103 ± .003 in 2.62 ± .08 mm			
100			Actual ID			
	Nominal (Inches)					
Size	ID	OD	in	±	mm	±
102	1/16	1/4	0.049	0.005	1.24	0.13
103	3/32	9/32	0.081	0.005	2.06	0.13
104	1/8	5/16	0.112	0.005	2.84	0.13
105	5/32	11/32	0.143	0.005	3.63	0.13
106	3/16	3/8	0.174	0.005	4.42	0.13
107	7/32	13/32	0.206	0.005	5.23	0.13
108	1/4	7/16	0.237	0.005	6.02	0.13
109	5/16	1/2	0.299	0.005	7.59	0.13
110	3/8	9/16	0.362	0.005	9.19	0.13
111	7/16	5/8	0.424	0.005	10.77	0.13
112	1/2	11/16	0.487	0.005	12.37	0.13
113	9/16	3/4	0.549	0.007	13.94	0.18
114	5/8	13/16	0.612	0.009	15.54	0.23
115	11/16	7/8	0.674	0.009	17.12	0.23
116	3/4	15/16	0.737	0.009	18.72	0.23
117	13/16	1	0.799	0.010	20.29	0.25
118	7/8	1-1/16	0.862	0.010	21.89	0.25
119	13/16	1-1/8	0.924	0.010	23.47	0.25
120	1	1-3/16	0.987	0.010	25.07	0.25
121	1-1/16	1-1/4	1.049	0.010	26.64	0.25
122	1-1/8	1-5/16	1.112	0.010	28.24	0.25
123	1-3/16	1-3/8	1.174	0.012	29.82	0.30
124	1-1/4	1-7/16	1.237	0.012	31.42	0.30
125	1-5/16	1-1/2	1.299	0.012	32.99	0.30
126	1-3/8	1-9/16	1.362	0.012	34.59	0.30
127	1-7/16	1-5/8	1.424	0.012	36.17	0.30
128	1-1/2	1-11/16	1.487	0.012	37.77	0.30
129	1-9/16	1-3/4	1.549	0.015	39.34	0.38
130	1-5/8	1-13/16	1.612	0.015	40.94	0.38
131	1-11/16	1-7/8	1.674	0.015	42.52	0.38
132	1-3/4	1-15/16	1.737	0.015	44.12	0.38
133	1-13/16	2	1.799	0.015	45.69	0.38
134	1-7/8	2-1/16	1.862	0.015	47.29	0.38
135	1-15/16	2-1/8	1.925	0.017	48.90	0.43
136	2	2-3/16	1.987	0.017	50.47	0.43
137	2-1/16	2-1/4	2.050	0.017	52.07	0.43
138	2-1/8	2-5/16	2.112	0.017	53.64	0.43
139	2-3/16	2-3/8	2.175	0.017	55.25	0.43
140	2-1/4	2-7/16	2.237	0.017	56.82	0.43
141	2-5/16	2-1/2	2.300	0.020	58.42	0.51

AS568 O-ring Reference guide.

ELPLASTO INNOVATIONS

Dash #	Nominal Cross Section: 3/32"		Actual: .103 ± .003 in 2.62 ± .08 mm			
100			Actual ID			
	Nominal (Inches)					
Size	ID	OD	in	±	mm	±
142	2-3/8	2-9/16	2.362	0.020	59.99	0.51
143	2-7/16	2-5/8	2.425	0.020	61.60	0.51
144	2-1/2	2-11/16	2.487	0.020	63.17	0.51
145	2-9/16	2-3/4	2.550	0.020	64.77	0.51
146	2-5/8	2-13/16	2.612	0.020	66.34	0.51
147	2-11/16	2-7/8	2.675	0.022	67.95	0.56
148	2-3/4	2-15/16	2.737	0.022	69.52	0.56
149	2-13/16	3	2.800	0.022	71.12	0.56
150	2-7/8	3-1/16	2.862	0.022	72.69	0.56
151	3	3-3/16	2.987	0.024	75.87	0.61
152	3-1/4	3-7/16	3.237	0.024	82.22	0.61
153	3-1/2	3-11/16	3.487	0.024	88.57	0.61
154	3-3/4	3-15/16	3.737	0.028	94.92	0.71
155	4	4-3/16	3.987	0.028	101.27	0.71
156	4-1/4	4-7/16	4.237	0.030	107.62	0.76
157	4-1/2	4-11/16	4.487	0.030	113.97	0.76
158	4-3/4	4-15/16	4.737	0.030	120.32	0.76
159	5	5-3/16	4.987	0.035	126.67	0.89
160	5-1/4	5-7/16	5.237	0.035	133.02	0.89
161	5-1/2	5-11/16	5.487	0.035	139.37	0.89
162	5-3/4	5-15/16	5.737	0.035	145.72	0.89
163	6	6-3/16	5.987	0.035	152.07	0.89
164	6-1/4	6-7/16	6.237	0.040	158.42	1.02
165	6-1/2	6-11/16	6.487	0.040	164.77	1.02
166	6-3/4	6-15/16	6.737	0.040	171.12	1.02
167	7	7-3/16	6.987	0.040	177.47	1.02
168	7-1/4	7-7/16	7.237	0.045	183.82	1.14
169	7-1/2	7-11/16	7.487	0.045	190.17	1.14
170	7-3/4	7-15/16	7.737	0.045	196.52	1.14
171	8	8-3/16	7.987	0.045	202.87	1.14
172	8-1/4	8-7/16	8.237	0.050	209.22	1.27
173	8-1/2	8-11/16	8.487	0.050	215.57	1.27
174	8-3/4	8-15/16	8.737	0.050	221.92	1.27
175	9	9-3/16	8.987	0.050	228.27	1.27
176	9-1/4	9-7/16	9.237	0.055	234.62	1.40
177	9-1/2	9-11/16	9.487	0.055	240.97	1.40
178	9-3/4	9-15/16	9.737	0.055	247.32	1.40

AS568 O-ring Reference guide.

ELPLASTO INNOVATIONS

Dash #	Nominal Cross Section: 1/8"		Actual: .139 ± .004 in 3.53 ± .10 mm			
200			Actual ID			
	Nominal (Inches)					
Size	ID	OD	in	±	mm	±
201	3/16	7/16	0.171	0.005	4.34	0.13
202	1/4	1/2	0.234	0.005	5.94	0.13
203	5/16	9/16	0.296	0.005	7.52	0.13
204	3/8	5/8	0.359	0.005	9.12	0.13
205	7/16	11/16	0.421	0.005	10.69	0.13
206	1/2	3/4	0.484	0.005	12.29	0.13
207	9/16	13/16	0.546	0.007	13.87	0.18
208	5/8	7/8	0.609	0.009	15.47	0.23
209	11/16	15/16	0.671	0.009	17.04	0.23
210	3/4	1	0.734	0.010	18.64	0.25
211	13/16	1-1/16	0.796	0.010	20.22	0.25
212	7/8	1-1/8	0.859	0.010	21.82	0.25
213	15/16	1-3/16	0.921	0.010	23.39	0.25
214	1	1-1/4	0.984	0.010	24.99	0.25
215	1-1/16	1-5/16	1.046	0.010	26.57	0.25
216	1-1/8	1-3/8	1.109	0.012	28.17	0.30
217	1-3/16	1-7/16	1.171	0.012	29.74	0.30
218	1-1/4	1-1/2	1.234	0.012	31.34	0.30
219	1-5/16	1-9/16	1.296	0.012	32.92	0.30
220	1-3/8	1-5/8	1.359	0.012	34.52	0.30
221	1-7/16	1-11/16	1.421	0.012	36.09	0.30
222	1-1/2	1-3/4	1.484	0.015	37.69	0.38
223	1-5/8	1-7/8	1.609	0.015	40.87	0.38
224	1-3/4	2	1.734	0.015	44.04	0.38
225	1-7/8	2-1/8	1.859	0.018	47.22	0.46
226	2	2-1/4	1.984	0.018	50.39	0.46
227	2-1/8	2-3/8	2.109	0.018	53.57	0.46
228	2-1/4	2-1/2	2.234	0.020	56.74	0.51
229	2-3/8	2-5/8	2.359	0.020	59.92	0.51
230	2-1/2	2-3/4	2.484	0.020	63.09	0.51
231	2-5/8	2-7/8	2.609	0.020	66.27	0.51
232	2-3/4	3	2.734	0.024	69.44	0.61
233	2-7/8	3-1/8	2.859	0.024	72.62	0.61
234	3	3-1/4	2.984	0.024	75.79	0.61
235	3-1/8	3-3/8	3.109	0.024	78.97	0.61
236	3-1/4	3-1/2	3.234	0.024	82.14	0.61
237	3-3/8	3-5/8	3.359	0.024	85.32	0.61
238	3-1/2	3-3/4	3.484	0.024	88.49	0.61
239	3-5/8	3-7/8	3.609	0.028	91.67	0.71
240	3-3/4	4	3.734	0.028	94.84	0.71
241	3-7/8	4-1/8	3.859	0.028	98.02	0.71
242	4	4-1/4	3.984	0.028	101.19	0.71
243	4-1/8	4-3/8	4.109	0.028	104.37	0.71
244	4-1/4	4-1/2	4.234	0.030	107.54	0.76
245	4-3/8	4-5/8	4.359	0.030	110.72	0.76

AS568 O-ring Reference guide.

ELPLASTO INNOVATIONS

Dash #	Nominal Cross Section: 1/8"		Actual: .139 ± .004 in 3.53 ± .10 mm			
200			Actual ID			
	Nominal (Inches)					
Size	ID	OD	in	±	mm	±
246	4-1/2	4-3/4	4.484	0.030	113.89	0.76
247	4-5/8	4-7/8	4.609	0.030	117.07	0.76
248	4-3/4	5	4.734	0.030	120.24	0.76
249	4-7/8	5-1/8	4.859	0.035	123.42	0.89
250	5	5-1/4	4.984	0.035	126.59	0.89
251	5-1/8	5-3/8	5.109	0.035	129.77	0.89
252	5-1/4	5-1/2	5.234	0.035	132.94	0.89
253	5-3/8	5-5/8	5.359	0.035	136.12	0.89
254	5-1/2	5-3/4	5.484	0.035	139.29	0.89
255	5-5/8	5-7/8	5.609	0.035	142.47	0.89
256	5-3/4	6	5.734	0.035	145.64	0.89
257	5-7/8	6-1/8	5.859	0.035	148.82	0.89
258	6	6-1/4	5.984	0.035	151.99	0.89
259	6-1/4	6-1/2	6.234	0.040	158.34	1.02
260	6-1/2	6-3/4	6.484	0.040	164.69	1.02
261	6-3/4	7	6.734	0.040	171.04	1.02
262	7	7-1/4	6.984	0.040	177.39	1.02
263	7-1/4	7-1/2	7.234	0.045	183.74	1.14
264	7-1/2	7-3/4	7.484	0.045	190.09	1.14
265	7-3/4	8	7.734	0.045	196.44	1.14
266	8	8-1/4	7.984	0.045	202.79	1.14
267	8-1/4	8-1/2	8.234	0.050	209.14	1.27
268	8-1/2	8-3/4	8.484	0.050	215.49	1.27
269	8-3/4	9	8.734	0.050	221.84	1.27
270	9	9-1/4	8.984	0.050	228.19	1.27
271	9-1/4	9-1/2	9.234	0.055	234.54	1.40
272	9-1/2	9-3/4	9.484	0.055	240.89	1.40
273	9-3/4	10	9.734	0.055	247.24	1.40
274	10	10-1/4	9.984	0.055	253.59	1.40
275	10-1/2	10-3/4	10.484	0.055	266.29	1.40
276	11	11-1/4	10.984	0.065	278.99	1.65
277	11-1/2	11-3/4	11.484	0.065	291.69	1.65
278	12	12-1/4	11.984	0.065	304.39	1.65
279	13	13-1/4	12.984	0.065	329.79	1.65
280	14	14-1/4	13.984	0.065	355.19	1.65
281	15	15-1/4	14.984	0.065	380.59	1.65
282	16	16-1/4	15.955	0.075	405.26	1.91
283	17	17-1/4	16.955	0.080	430.66	2.03
284	18	18-1/4	17.955	0.085	456.06	2.16

AS568 O-ring Reference guide.

ELPLASTO INNOVATIONS

Dash #	Nominal Cross Section: 3/16"		Actual: .210 ± .005 in 5.33 ± .13 mm			
300			Actual ID			
	Nominal (Inches)					
Size	ID	OD	in	±	mm	±
309	7/16	13/16	0.412	0.005	10.46	0.13
310	1/2	7/8	0.475	0.005	12.07	0.13
311	9/16	15/16	0.537	0.007	13.64	0.18
312	5/8	1	0.600	0.009	15.24	0.23
313	11/16	1-1/16	0.662	0.009	16.81	0.23
314	3/4	1-1/8	0.725	0.010	18.42	0.25
315	13/16	1-3/16	0.787	0.010	19.99	0.25
316	7/8	1-1/4	0.850	0.010	21.59	0.25
317	15/16	1-5/16	0.912	0.010	23.16	0.25
318	1	1-3/8	0.975	0.010	24.77	0.25
319	1-1/16	1-7/16	1.037	0.010	26.34	0.25
320	1-1/8	1-1/2	1.100	0.012	27.94	0.30
321	1-3/16	1-9/16	1.162	0.012	29.51	0.30
322	1-1/4	1-5/8	1.225	0.012	31.12	0.30
323	1-5/16	1-11/16	1.287	0.012	32.69	0.30
324	1-3/8	1-3/4	1.350	0.012	34.29	0.30
325	1-1/2	1-7/8	1.475	0.015	37.47	0.38
326	1-5/8	2	1.600	0.015	40.64	0.38
327	1-3/4	2-1/8	1.725	0.015	43.82	0.38
328	1-7/8	2-1/4	1.850	0.015	46.99	0.38
329	2	2-3/8	1.975	0.018	50.17	0.46
330	2-1/8	2-1/2	2.100	0.018	53.34	0.46
331	2-1/4	2-5/8	2.225	0.018	56.52	0.46
332	2-3/8	2-3/4	2.350	0.018	59.69	0.46
333	2-1/2	2-7/8	2.475	0.020	62.87	0.51
334	2-5/8	3	2.600	0.020	66.04	0.51
335	2-3/4	3-1/8	2.725	0.020	69.22	0.51
336	2-7/8	3-1/4	2.850	0.020	72.39	0.51
337	3	3-3/8	2.975	0.024	75.57	0.61
338	3-1/8	3-1/2	3.100	0.024	78.74	0.61
339	3-1/4	3-5/8	3.225	0.024	81.92	0.61
340	3-3/8	3-3/4	3.350	0.024	85.09	0.61
341	3-1/2	3-7/8	3.475	0.024	88.27	0.61
342	3-5/8	4	3.600	0.028	91.44	0.71
343	3-3/4	4-1/8	3.725	0.028	94.62	0.71
344	3-7/8	4-1/4	3.850	0.028	97.79	0.71
345	4	4-3/8	3.975	0.028	100.97	0.71
346	4-1/8	4-1/2	4.100	0.028	104.14	0.71
347	4-1/4	4-5/8	4.225	0.030	107.32	0.76
348	4-3/8	4-3/4	4.350	0.030	110.49	0.76
349	4-1/2	4-7/8	4.475	0.030	113.67	0.76
350	4-5/8	5	4.600	0.030	116.84	0.76
351	4-3/4	5-1/8	4.725	0.030	120.02	0.76
352	4-7/8	5-1/4	4.850	0.030	123.19	0.76
353	5	5-3/8	4.975	0.037	126.37	0.94

AS568 O-ring Reference guide.

ELPLASTO INNOVATIONS

Dash #	Nominal Cross Section: 3/16"		Actual: .210 ± .005 in 5.33 ± .13 mm			
300			Actual ID			
	Nominal (Inches)					
Size	ID	OD	in	±	mm	±
354	5-1/8	5-1/2	5.100	0.037	129.54	0.94
355	5-1/4	5-5/8	5.225	0.037	132.72	0.94
356	5-3/8	5-3/4	5.350	0.037	135.89	0.94
357	5-1/2	5-7/8	5.475	0.037	139.07	0.94
358	5-5/8	6	5.600	0.037	142.24	0.94
359	5-3/4	6-1/8	5.725	0.037	145.42	0.94
360	5-7/8	6-1/4	5.850	0.037	148.59	0.94
361	6	6-3/8	5.975	0.037	151.77	0.94
362	6-1/4	6-5/8	6.225	0.040	158.12	1.02
363	6-1/2	6-7/8	6.475	0.040	164.47	1.02
364	6-3/4	7-1/8	6.725	0.040	170.82	1.02
365	7	7-3/8	6.975	0.040	177.17	1.02
366	7-1/4	7-5/8	7.225	0.045	183.52	1.14
367	7-1/2	7-7/8	7.475	0.045	189.87	1.14
368	7-3/4	8-1/8	7.725	0.045	196.22	1.14
369	8	8-3/8	7.975	0.045	202.57	1.14
370	8-1/4	8-5/8	8.225	0.050	208.92	1.27
371	8-1/2	8-7/8	8.475	0.050	215.27	1.27
372	8-3/4	9-1/8	8.725	0.050	221.62	1.27
373	9	9-3/8	8.975	0.050	227.97	1.27
374	9-1/4	9-5/8	9.225	0.055	234.32	1.40
375	9-1/2	9-7/8	9.475	0.055	240.67	1.40
376	4-1/2	5	9.725	0.055	247.02	1.40
377	4-5/8	5-1/8	9.975	0.055	253.37	1.40
378	4-3/4	5-1/4	10.475	0.060	266.07	1.52
379	4-7/8	5-3/8	10.975	0.060	278.77	1.52
380	5	5-1/2	11.475	0.065	291.47	1.65
381	5-1/8	5-5/8	11.975	0.065	304.17	1.65
382	5-1/4	5-3/4	12.975	0.065	329.57	1.65
383	5-3/8	5-7/8	13.975	0.070	354.97	1.78
384	5-1/2	6	14.975	0.070	380.37	1.78
385	5-5/8	6-1/8	15.955	0.075	405.26	1.91
386	5-3/4	6-1/4	16.955	0.080	430.66	2.03
387	5-7/8	6-3/8	17.955	0.085	456.06	2.16
388	6	6-1/2	18.955	0.090	481.45	2.29
389	6-1/4	6-3/4	19.955	0.095	506.85	2.41
390	6-1/2	7	20.955	0.095	532.25	2.41
391	6-3/4	7-1/4	21.955	0.100	557.65	2.54
392	7	7-1/2	22.940	0.105	582.68	2.67
393	7-1/4	7-3/4	23.940	0.110	608.08	2.79
394	7-1/2	8	24.940	0.115	633.48	2.92
395	7-3/4	8-1/4	25.940	0.120	658.88	3.05

AS568 O-ring Reference guide.

ELPLASTO INNOVATIONS

Dash #	Nominal Cross Section: 1/4"		Actual: .275 ± .006 in 6.99 ± .15 mm			
400			Actual ID			
	Nominal (Inches)					
Size	ID	OD	in	±	mm	±
400	1-3/8	1-7/8	1.350	0.012	34.29	0.30
401	1-1/2	2	1.475	0.014	37.47	0.36
402	1-5/8	2-1/8	1.600	0.015	40.64	0.38
403	1-3/4	2-1/4	1.725	0.015	43.82	0.38
404	1-7/8	2-3/8	1.850	0.015	46.99	0.38
405	2	2-1/2	1.975	0.018	50.17	0.46
406	2-1/8	2-5/8	2.100	0.018	53.34	0.46
407	2-1/4	2-3/4	2.225	0.018	56.52	0.46
408	2-3/8	2-7/8	2.350	0.018	59.69	0.46
409	2-1/2	3	2.475	0.020	62.87	0.51
410	2-5/8	3-1/8	2.600	0.020	66.04	0.51
411	2-3/4	3-1/4	2.725	0.020	69.22	0.51
412	2-7/8	3-3/8	2.850	0.020	72.39	0.51
413	3	3-1/2	2.975	0.024	75.57	0.61
414	3-1/8	3-5/8	3.100	0.024	78.74	0.61
415	3-1/4	3-3/4	3.225	0.024	81.92	0.61
416	3-3/8	3-7/8	3.350	0.024	85.09	0.61
417	3-1/2	4	3.475	0.024	88.27	0.61
418	3-5/8	4-1/8	3.600	0.028	91.44	0.71
419	3-3/4	4-1/4	3.725	0.028	94.62	0.71
420	3-7/8	4-3/8	3.850	0.028	97.79	0.71
421	4	4-1/2	3.975	0.028	100.97	0.71
422	4-1/8	4-5/8	4.100	0.028	104.14	0.71
423	4-1/4	4-3/4	4.225	0.030	107.32	0.76
424	4-3/8	4-7/8	4.350	0.030	110.49	0.76
425	4-1/2	5	4.475	0.033	113.67	0.84
426	4-5/8	5-1/8	4.600	0.033	116.84	0.84
427	4-3/4	5-1/4	4.725	0.033	120.02	0.84
428	4-7/8	5-3/8	4.850	0.033	123.19	0.84
429	5	5-1/2	4.975	0.037	126.37	0.94
430	5-1/8	5-5/8	5.100	0.037	129.54	0.94
431	5-1/4	5-3/4	5.225	0.037	132.72	0.94
432	5-3/8	5-7/8	5.350	0.037	135.89	0.94
433	5-1/2	6	5.475	0.037	139.07	0.94
434	5-5/8	6-1/8	5.600	0.037	142.24	0.94
435	5-3/4	6-1/4	5.725	0.037	145.42	0.94
436	5-7/8	6-3/8	5.850	0.037	148.59	0.94
437	6	6-1/2	5.975	0.037	151.77	0.94
438	6-1/4	6-3/4	6.225	0.040	158.12	1.02
439	6-1/2	7	6.475	0.040	164.47	1.02
440	6-3/4	7-1/4	6.725	0.040	170.82	1.02
441	7	7-1/2	6.975	0.040	177.17	1.02
442	7-1/4	7-3/4	7.225	0.045	183.52	1.14
443	7-1/2	8	7.475	0.045	189.87	1.14
444	7-3/4	8-1/4	7.725	0.045	196.22	1.14

AS568 O-ring Reference guide.

ELPLASTO INNOVATIONS

Dash #	Nominal Cross Section: 1/4"		Actual: .275 ± .006 in 6.99 ± .15 mm			
400			Actual ID			
	Nominal (Inches)					
Size	ID	OD	in	±	mm	±
445	8	8-1/2	7.975	0.045	202.57	1.14
446	8-1/2	9	8.475	0.055	215.27	1.40
447	9	9-1/2	8.975	0.055	227.97	1.40
448	9-1/2	10	9.475	0.055	240.67	1.40
449	10	10-1/2	9.975	0.055	253.37	1.40
450	10-1/2	11	10.475	0.060	266.07	1.52
451	11	11-1/2	10.975	0.060	278.77	1.52
452	11-1/2	12	11.475	0.060	291.47	1.52
453	12	12-1/2	11.975	0.060	304.17	1.52
454	12-1/2	13	12.475	0.060	316.87	1.52
455	13	13-1/2	12.975	0.060	329.57	1.52
456	13-1/2	14	13.475	0.070	342.27	1.78
457	14	14-1/2	13.975	0.070	354.97	1.78
458	14-1/2	15	14.475	0.070	367.67	1.78
459	15	15-1/2	14.975	0.070	380.37	1.78
460	15-1/2	16	15.475	0.070	393.07	1.78
461	16	16-1/2	15.955	0.075	405.26	1.91
462	16-1/2	17	16.455	0.075	417.96	1.91
463	17	17-1/2	16.955	0.080	430.66	2.03
464	17-1/2	18	17.455	0.085	443.36	2.16
465	18	18-1/2	17.955	0.085	456.06	2.16
466	18-1/2	19	18.455	0.085	468.76	2.16
467	19	19-1/2	18.955	0.090	481.46	2.29
468	19-1/2	20	19.455	0.090	494.16	2.29
469	20	20-1/2	19.955	0.095	506.86	2.41
470	21	21-1/2	20.955	0.095	532.26	2.41
471	22	22-1/2	21.955	0.100	557.66	2.54
472	23	23-1/2	22.940	0.105	582.68	2.67
473	24	24-1/2	23.940	0.110	608.08	2.79
474	25	25-1/2	24.940	0.115	633.48	2.92
475	26	26-1/2	25.940	0.120	658.88	3.05